TECHNISCHES DATENBLATT



Air Velocity Transmitter

> Typ EMIVLJ

IVLJ 10 transmitter is designed for HVAC applications. Output signals correspond to the air flow velocity and temperature inside the ventilation duct.

Probe of the transmitter is mounted in the duct, on a place where the air flow is as laminar as possible. The transmitter should be mounted a suitable place near the probe. Linear and air flow proportional measuring signal is produced by comparing the sensor element temperatures. Both outputs can be separately selected to be either 4...20 mA or 0...10 V outputs.

The N model display resolution is 0,1 m/s for velocity and 0,1 °C for temperature. The display can be added also after commissioning. The measurement values scroll on the display. The wanted value can be locked to view continuously by removing the jumper on back of the display board.

IVLJ 10 is also available with a 100 and 400 mm long probe stem.

Output signal selection



Wiring





Technical data

Supply 24 Vac (22...28 V), < 1.5 VA 24 Vdc (23...28 V), < 1.5 W

Ranges

velocity 0...10 m/s temperature 0...50 °C

Accuracy

measuring range $< 0.5 \text{ m/s} \pm 7 \% \text{ from reading (at 25 °C)}$

 $< 0.5 \, ^{\circ}\text{C} \, (25 \, ^{\circ}\text{C}, > 0.5 \, \text{m/s})$ temperature

0...10 V, < 2 mA, Outputs $4...20 \text{ mA}, < 600 \Omega$

Probe cable 2 m

Ambient temperature 0...50 °C

Mounting

probe by a flange, adjustable depth (200 mm

stem)

with screws, external lugs transmitter Protection class IP 54 (transmitter), cable glands

downwards

Materials PBT, PC, PA and stainless steel

Ordering guide: Model Product number Description IVLJ 10 1130090 air flow transmitter 0...10 m/s, immersion depth 50...190 mm IVLJ 10-100 1130091 air flow transmitter, immersion depth 50...90 mm IVLJ 10-400 1130095 air flow transmitter, immersion depth 50...390 mm

Products fulfil the requirements of directive 2004/108/EC and are in accordance with the standards EN61000-6-3: 2001 (Emission) and EN61000-6-2: 2001 (Immunity).